



DATA SHEET

# Clima Sensor - Multi-talented in Meteorology



Intelligent Measurement & Testing

## Wide Variety of Measurement Data thanks to Ultrasound

Use our ultrasonic climate sensors to log numerous data, depending on the configuration level:

- Wind speed and direction
- Type and quantity of precipitation
- Brightness and dusk
- Ambient temperature
- Relative humidity
- Air pressure

The measured variables are provided via both analogue outputs and an RS422/485 interface (ASCII/MODBUS). The advantage of these combined sensors is their simple, space-saving installation with no complex mechanical support structures, which ensures an excellent price-performance ratio.

### Benefits & Features

- Compact sensor unit to measure a number of meteorological variables
- Highly durable, no moving parts
- Precise measurement of meteorological variables
- Measurement of wind speed and direction by ultrasound (Ultrasonic, US)
- Output: RS485 / MODBUS or 10 V signals
- Integrated GPS receiver
- Developed and manufactured in Germany

### Type Overview

Type	US WIND	US TFB	US NH	US NHTFB
<b>Measurement Parameter</b>				
Wind speed, 0 to 60 m/s	X	X	X	X
Wind direction, 0 to 360°	X	X	X	X
Precipitation intensity, 0.001 to 10 mm/min.			X	X
Precipitation type			X	X
Brightness, 0 to 150 kLux			X	X
Ambient temperature, -30 to +70 °C		X		X
Relative air humidity, 0 to 100 %rH		X		X
Barometric pressure, 300 to 1100 hPa		X		X

## Technical Data

### All Types

Output signal	RS485 / MODBUS, analog 0 to 10 V for each measurement parameter
Voltage supply	5 to 30 V <sub>DC</sub>
Heating	24 VAC/V <sub>DC</sub> / 25 VA
Operating temperature	-30 to +70 °C
Degree of protection	IP66
Customs tariff number	90 15 80 20

## Accessories

Clima Sensor US Cable serial	8-core cable for data acquisition by RS485 / MODBUS
Cable Clima Sensor US analog + serial	16-core cable for data acquisition by RS485 / MODBUS and 10 V signals

## Scope of Delivery

All types	Instruction manual
-----------	--------------------